

Pg. 1 of 8

MATERIAL SAFETY DATA SHEET

Version:02

PRODUCT NAME: PROPAN-2-OL (ISO PROPYL ALCOHOL) CAS Number: 67-63-0

IDENTIFICATION:

90044, 90096, 90226, 90520, 90706, 90733, 90786, 90897, 91635, 91893, 94047, 94101, **Product Code**

98112, 999001

Company Name ADVENT CHEMBIO PRIVATE LIMITED

W-279, MIDC, TTC INDUSTRIAL AREA, THANE-BELAPUR ROAD, RABALE, Address

NAVI MUMBAI - 400 701, MAHARASHTRA, INDIA.

E-mail sales@adventchembio.com

WEBSITE www.adventchembio.com

Company Phone Number +91 77770 84837

HAZARDS IDENTIFICATION:

Hazard classification

Physical hazards

Flammable liquids Category 2

Health hazards

Hazard symbol

Serious eye damage/eye

irritation

Category 2

Specific target organ

toxicity - single exposure

Category 3

Labels elements



Signal word Danger

Hazard statement Highly flammable liquid and vapor.

Causes serious eye irritation.

May cause drowsiness or dizziness.

Precautionary statement

Prevention : Obtain special instructions before use.

Do not breathe dust/ fume/ gas/ mist/ vapors/ spray. Do not handle until all safety

precautions have been read and understood.

Wear protective gloves/ protective clothing/ eye protection/ face protection. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.

Keep container tightly closed. Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools. Take precautionary measures against static discharge.

Response IF exposed or concerned: Get medical advice/ attention.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/

shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.



Pg. 2 of 8

Version:02

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: PROPAN-2-OL (ISO PROPYL ALCOHOL) CAS Number: 67-63-0

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

Storage : Store in a dry & well-ventilated place. Keep container tightly closed. Containers which are

opened must be carefully resealed and kept upright to prevent leakage.

Disposal : Dispose of contents/container to an appropriate treatment and disposal facility in

accordance with applicable laws and regulations, and product characteristics at time of

disposal.

Other hazards which do not : result in GHS classification

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or

explosion.

3. COMPOSITION/INFORMATION ON INGRADIENTS:

| Ingredient | CAS Number | Percent | Hazardous |
|-------------------|------------|-----------|-----------|
| Isopropyl Alcohol | 67-63-0 | 99 - 100% | Yes |

4. FIRST AID MEASURES:

General information : Get medical advice/attention if you feel unwell. Show this safety data sheet to the doctor in

attendance.

Ingestion Call a physician or poison control center immediately. Rinse mouth. Do NOT induce

: vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the

lungs.

Move to fresh air. Call a physician or poison control center immediately. If breathing stops,

Toxic if inhaled. Toxic if swallowed. Toxic in contact with skin. Irritating to eyes, respiratory

Inhalation : provide artificial respiration. If breathing is difficult, give oxygen.

Get medical attention if symptoms persist.

Skin contact Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact

lenses. Get medical attention.

Eye contact Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact

lenses. Get medical attention.

system and skin.

Most important

symptoms/effects, acute

and delayed

Indication of immediate

medical attention and special treatment needed

: Symptoms may be delayed. Treat symptomatically.

5. FIRE FIGHTING MEASURES:

General information

Flammable liquid and vapor.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media

Water spray, foam, dry powder or carbon dioxide.

Unsuitable extinguishing

media

: Avoid water in straight hose stream; will scatter and spread fire.

Specific hazards arising from the chemical

Vapors may cause a flash fire or ignite explosively. Vapors may travel considerable distance

to a source of ignition and flash back. Prevent buildup of vapors or gases to explosive

concentrations. Vapor from the solvent may accumulate in container headspace resulting in flammability hazard. Heat may cause the containers to explode.



MATERIAL SAFETY DATA SHEET

Version:02

Pg. 3 of 8

PRODUCT NAME: PROPAN-2-OL (ISO PROPYL ALCOHOL) CAS Number: 67-63-0

Special protective equipment and precautions for firefighters

Special firefighting Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting procedures

the fire. Fight fire from a protected location. Move containers from fire area if you can do so

without risk.

Firefighters must use standard protective equipment including flame retardant coat, helmet Special protective

equipment for fire-fighters with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

ACCIDENTAL RELEASE MEASURES:

Personal precautions, protective equipment and emergency procedures

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Avoid breathing mists or vapors. Keep upwind. Ventilate closed spaces before entering them. Do not touch damaged containers or spilled material unless wearing appropriate

protective clothing. Keep unauthorized personnel away.

Methods and material for containment and cleaning up

Eliminate all ignition sources if safe to do so. Use only non-sparking tools. Take precautionary measures against static discharges. Stop leak if possible without any risk.

Absorb spill with vermiculite or other inert material, then place in a container for chemical waste. Clean surface thoroughly to remove residual contamination. Dike far ahead of larger spill for later recovery and disposal.

Notification Procedures

Prevent entry into waterways, sewer, basements or confined areas. Inform authorities if

large amounts are involved.

Environmental precautions

Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do

so. Avoid discharge into drains, water courses or onto the ground.

HANDLING AND STORAGE:

Precautions for safe handling

Do not handle until all safety precautions have been read and understood. DO NOT handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Take precautionary measures against static discharges. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Wear protective gloves/protective clothing/eye

protection/ face protection. Avoid contact with eyes, skin, and clothing. Do not breathe mist or vapor. Use only with adequate ventilation. Wash hands thoroughly after handling.

Conditions for safe storage,

including any incompatibilities

Keep away from food, drink and animal feeding stuffs. Keep container tightly closed in a dry, well-ventilated place. Ground container and transfer equipment to eliminate static electric sparks. Comply with all national, state, and local codes pertaining to the storage, handling,

dispensing, and disposal of flammable liquids.

EXPOSURE CONTROLS PERSONAL PROTECTION:

Control parameters

Occupational exposure

limits

Chemical identity Exposure Limit values Source Type

ISOPROPYL ALCOHOL **TWA** 200 ppm US. ACGIH Threshold Limit Values (2011)

> STEL 400 ppm US. ACGIH Threshold Limit Values (2011)



Pg. 4 of 8

Version:02

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: PROPAN-2-OL (ISO PROPYL ALCOHOL) CAS Number: 67-63-0

REL 400 ppm 980 mg/m³ US. NIOSH: Pocket Guide to Chemical

Hazards (2010)

STEL 500 ppm 1,225 mg/m³ US. NIOSH: Pocket Guide to Chemical

Hazards (2010)

PEL 400 ppm 980 mg/m³ US. OSHA Table Z-1 Limits for Air

Contaminants (29 CFR 1910.1000) (02

2006)

TWA 400 ppm 980 mg/m³ US. OSHA Table Z-1-A (29 CFR

1910.1000)(1989)

STEL 500 ppm 1,225 mg/m³ US. OSHA Table Z-1-A (29 CFR

1910.1000) (1989)

Appropriate engineering

General information

Eye/face protection

Hygiene measures

controls : No data available

Individual protection measures, such as personal protective equipment

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust

ventilation, or other engineering controls to maintain airborne levels below recommended

exposure limits. If exposure limits have not been established, maintain airborne levels to an

acceptable level. An eye wash and safety shower must be available in the immediate work

area. Use explosion-proof ventilation equipment.Wear safety glasses with side shields (or goggles).

Hand protection . Chemical resistant gloves.

Other . Wear suitable protective clothing.

Respiratory protection In case of inadequate ventilation use suitable respirator. Chemical

respirator with organic vapor cartridge.

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and

protective equipment to remove contaminants. Provide eyewash station and safety shower.

Avoid contact with eyes, skin, and clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES:

Appearance : Clear, colorless liquid

Odor : Alcohol type

Solubility : Miscible in water.

Molecular Weight : 60.10 g/mol

Specific Gravity : 0.785 g/cm3 at 25°C

pH : No information found.

% Volatiles by volume @

21C (70F) : 100



Pg. 5 of 8

Version:02

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: PROPAN-2-OL (ISO PROPYL ALCOHOL) CAS Number: 67-63-0

 Boiling Point
 : 82°C

 Melting Point
 : -89.5°C

 Flash Point
 : 12 °C

 Vapor Density (Air=1)
 : 2.1

Vapor Pressure (mm Hg) : 44 @ 25°C

Evaporation Rate (BuAc=1) : 3.0

10. STABILITY AND REACTIVITY:

Reactivity: No dangerous reaction known under conditions of normal use.

Chemical stability : Material is stable under normal conditions..

Possibility of hazardous

reactions

: Hazardous polymerization does not occur.

Conditions to avoid : Heat, sparks, flames. Sunlight.

Incompatible materials

Strong oxidizing agents. Acetaldehyde. Acids. Chlorine. Ethylene Oxide

Hydrogen peroxide (H2O2) Sulfuric acid. Isocyanates. Aluminum.

Hazardous decomposition

products

: Thermal decomposition may release oxides of carbon.

11. TOXICOLOGICAL INFORMATION:

Information on likely routes of exposure

Ingestion : Irritating. May cause nausea, stomach pain and vomiting.

Inhalation May cause irritation to the mucous membranes and upper respiratory tract. May cause

central nervous system effects

Skin contact : Causes mild skin irritation

Eye contact : Causes serious eye irritation.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral Product : LD 50 (Rat): 5,045 mg/kg

Dermal Product : LD 50 (Rabbit): 12,800 mg/kg

Inhalation Product . No data available.

Repeated dose toxicity

Product

No data available.

Skin corrosion/irritation

Product

Prolonged or repeated skin contact may cause drying, cracking, or irritation

Serious eye damage/eye

irritation Product

: Irritating to eyes.

Respiratory or skin

sensitization Product : NO

: Not a skin sensitizer.



Pg. 6 of 8

MATERIAL SAFETY DATA SHEET

CAS Number: 67-63-0

Version:02

PRODUCT NAME: PROPAN-2-OL (ISO PROPYL ALCOHOL)

Carcinogenicity Product : This substance has no evidence of carcinogenic properties

IARC Monographs on the

Evaluation of Carcinogenic

Risks to Humans

US. National Toxicology

Program (NTP) Report on

Carcinogens

US. OSHA Specifically

Regulated Substances (29 CFR 1910.1001-1050

Germ cell mutagenicity

: No carcinogenic components identified.

: No carcinogenic components identified.

: No carcinogenic components identified.

No components toxic to reproduction.

In vitro Product : No data available.

Reproductive toxicity

Product

Specific target organ

toxicity - single exposure

Product

Specific target organ

toxicity - repeated

exposure Product

Aspiration hazard Product

None known.

Not known.

May be harmful if swallowed and enters airways.

Other effects : None known.

12. ECOLOGICAL INFORMATION:

Ecotoxicity

Acute hazards to the aquatic environment

Fish Product : LC 50 (Western mosquitofish (Gambusia affinis), 96 h): > 1,400 mg/l.

Aquatic invertebrates

Product

: LC 50 (Water flea (Daphnia magna), 24 h): 10,000 mg/l.

Chronic hazards to the aquatic environment

Fish Product : No data available.

Aquatic invertebrates

Product

: No data available.

Toxicity to Aquatic Plants

Product:

: No data available.

Persistence and degradability

Biodegradation Product : Expected to be readily biodegradable.

BOD/COD ratio Product : No data available.

Bioaccumulative potential



Pg. 7 of 8

MATERIAL SAFETY DATA SHEET

Version:02

PRODUCT NAME: PROPAN-2-OL (ISO PROPYL ALCOHOL)

Bioconcentration factor

(BCF) Product

No data available on bioaccumulation.

Partition coefficient n-

octanol / water (log Kow)

: No data available.

Product

Specified substance(s)

ACETONITRILE

: Log Kow: 0.05

Mobility in soil

: The product is partly soluble in water. May spread in the aquatic environment.

Other adverse effects

The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging

CAS Number: 67-63-0

effect on the environment.

13. DISPOSAL CONSIDERATION:

Discharge, treatment, or disposal may be subject to national, state, or local laws. Disposal

recommendations are based on uncontaminated material.

Contaminated packaging Since emptied containers retain product residue, follow label warnings even after container

is emptied.

14. TRANSPORT INFORMATION:

| DOT | UN No. UN 1219 | UN proper shipping name Isopropyl Alcohol | Hazard Class(es) 3 | Packaging group II | Marine Pollutant No |
|------|-------------------|---|--------------------------|--------------------------|---------------------------|
| IMDG | UN 1219 | Isopropyl Alcohol | 3 | II | No |
| IATA | UN 1219 | Isopropyl Alcohol | 3 | II | No |

15. REGULATORY INFORMATION:

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006. Safety, health and environmental regulations/legislation specific for the substance or mixture No Data Available.



Pg. 8 of 8

Version:02

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: PROPAN-2-OL (ISO PROPYL ALCOHOL) CAS Number: 67-63-0

16. OTHER INFORMATION:

NFPA Hazard ID

: 2 0 Flammability
Health
Reactivity
Special hazard.

Hazard rating: 0 - Minimal; 1 - Slight; 2 - Moderate; 3 - Serious; 4 - Severe

Issue Date : 01/01/2025

Version Number : 02

Disclaimer: This Material Safety Data Sheet (MSDS) is for guidance and is based upon information and tests believed to be reliable. ADVENT CHEMBIO PRIVATE LIMITED makes no guarantee of the accuracy or completeness of the data and shall not be liable for any damages relating thereto. The data is offered solely for your consideration, investigation, and verification. The data should not be confused with local, state, federal or insurance mandates, regulations, or requirements and CONSTITUTE NO WARRANTY. Any use of this data and information must be determined by the technical instructor in accordance with applicable local, state or federal laws and regulations. The conditions or methods of handling, storage, use and disposal of the product(s) described are beyond the control of ADVENT CHEMBIO PRIVATE LIMITED and may be beyond our knowledge. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH THE HANDLING, STORAGE, USE OR DISPOSAL OF THIS PRODUCT(S).