



MATERIAL SAFETY DATA SHEET

Version :02

PRODUCT NAME: iso-BUTANOL (iso-BUTYL ALCOHOL)

CAS Number: 78-83-1

1. IDENTIFICATION:

Product Code : 91521, 93174, 94052, 95208, 98708, 98153

Company Name : ADVENT CHEMBIO PRIVATE LIMITED

Address : W-279, MIDC, TTC INDUSTRIAL AREA, THANE-BELAPUR ROAD, RABALE,
NAVI MUMBAI - 400 701, MAHARASHTRA, INDIA.

E-mail : sales@adventchembio.com

WEBSITE : www.adventchembio.com

Company Phone Number : +91 77770 84837

2. HAZARDS IDENTIFICATION:**Hazard classification****Physical hazards**

Flammable liquids : Category 3 (Flammable liquid and vapor.)

Health hazards

Skin irritation : Category 2 (Causes skin irritation.)

Serious eye damage : Category 1 (Causes serious eye damage)

Specific target organ toxicity - single exposure : Category 3 (May cause drowsiness or dizziness.)

Central nervous system

Specific target organ toxicity - single exposure : Category 3 (May cause respiratory irritation.)

Respiratory system

Labels elements :

Hazard symbol :



Signal word : Danger

Hazard statement

Flammable liquid and vapor.
Causes serious eye damage
: May cause drowsiness or dizziness.
May cause respiratory irritation
Causes skin irritation.

Precautionary statement

Prevention

: Obtain special instructions before use.
Do not breathe dust/ fume/ gas/ mist/ vapors/ spray. Do not handle until all safety precautions have been read and understood.
Wear protective gloves/ protective clothing/ eye protection/ face protection.
Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
Keep container tightly closed. Ground/ bond container and receiving equipment.



MATERIAL SAFETY DATA SHEET

Version :02

PRODUCT NAME: iso-BUTANOL (iso-BUTYL ALCOHOL)

CAS Number: 78-83-1

Response	:	Use explosion-proof electrical/ ventilating/ lighting/ equipment.
		Use only non-sparking tools. Take precautionary measures against static discharge.
Storage	:	IF exposed or concerned: Get medical advice/ attention.
		IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
Disposal	:	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
		Store in a dry & well-ventilated place. Keep container tightly closed. Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Other hazards which do not result in GHS classification	:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
		This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

3. COMPOSITION/ INFORMATION ON INGREDIENTS:

Ingredient	CAS Number	Percent	Hazardous
Iso-Butanol (Iso-Butyl alcohol)	78-83-1	NLT 98.5%	Yes

4. FIRST AID MEASURES:

General information	:	Get medical advice/attention if you feel unwell. Show this safety data sheet to the doctor in attendance.
Ingestion	:	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Inhalation	:	Move to fresh air. Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. If breathing is difficult, give oxygen.
Skin contact	:	Get medical attention if symptoms persist.
Eye contact	:	Immediately flush with plenty of water for at least 15 minutes. Get medical attention.
Most important symptoms/effects, acute and delayed	:	Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.
Indication of immediate medical attention and special treatment needed	:	The most important known symptoms and effects are described in the labelling.
	:	No data available.

5. FIRE FIGHTING MEASURES:

General information	:	Flammable liquid and vapor.
Suitable (and unsuitable) extinguishing media	:	
Suitable extinguishing media	:	Carbon dioxide (CO2) Foam Dry powder.



MATERIAL SAFETY DATA SHEET

Version :02

PRODUCT NAME: iso-BUTANOL (iso-BUTYL ALCOHOL)

CAS Number: 78-83-1

Unsuitable extinguishing media : For this substance/mixture no limitations of extinguishing agents are given.

Specific hazards arising from the chemical : Vapors may cause a flash fire or ignite explosively. Vapors may travel considerable distance to a source of ignition and flash back. Prevent buildup of vapors or gases to explosive concentrations. Vapor from the solvent may accumulate in container headspace resulting in flammability hazard. Heat may cause the containers to explode.

Special protective equipment and precautions for firefighters

Special firefighting procedures : Fight fire from a protected location. Move containers from fire area if you can do so without risk.

Special protective equipment for fire-fighters : Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. ACCIDENTAL RELEASE MEASURES:

Personal precautions, protective equipment and emergency procedures : ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Avoid breathing mists or vapors. Keep upwind. Ventilate closed spaces before entering them. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

Methods and material for containment and cleaning up : Eliminate all ignition sources if safe to do so. Use only non-sparking tools. Take precautionary measures against static discharges. Stop leak if possible without any risk. Absorb spill with vermiculite or other inert material, then place in a container for chemical waste. Clean surface thoroughly to remove residual contamination. Dike far ahead of larger spill for later recovery and disposal.

Notification Procedures : Prevent entry into waterways, sewer, basements or confined areas. Inform authorities if large amounts are involved.

Environmental precautions : Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Risk of explosion.

7. HANDLING AND STORAGE:

Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Take precautionary measures against static discharges. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Wear protective gloves/protective clothing/eye protection/ face protection. Avoid contact with eyes, skin, and clothing. Do not breathe mist or vapor. Use only with adequate ventilation. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities : Keep away from food, drink and animal feeding stuffs. Keep container tightly closed in a dry, well-ventilated place. Ground container and transfer equipment to eliminate static electric sparks.



MATERIAL SAFETY DATA SHEET

Version :02

PRODUCT NAME: iso-BUTANOL (iso-BUTYL ALCOHOL)

CAS Number: 78-83-1

8. EXPOSURE CONTROLS PERSONAL PROTECTION:**Appropriate engineering****controls**

: No data available

Derived No Effect Level**(DNEL)**: **Ingredients with workplace control parameters :**

Application Area	Routes of exposure	Health effect	Value
Worker DNEL, long term	inhalation	Long-term local effects	310 mg/m3
Consumer DNEL, long term	oral	Long-term systemic effects	
Consumer DNEL, long term	inhalation	Long-term local effects	55 mg/m3
Compartment		Value	
Fresh water		0,4 mg/l	
Sea water		0,04 mg/l	
Aquatic intermittent release		11 mg/l	
Fresh water sediment		1,52 mg/kg	
Sea sediment		0,152 mg/kg	
Soil		0,07 mg/kg	
Sewage treatment plant		10 mg/l	

Predicted No Effect**Concentration (PNEC)**

:

Individual protection measures, such as personal protective equipment**General information**

:

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. An eye wash and safety shower must be available in the immediate work area. Use explosion-proof ventilation equipment.

Eye/face protection

:

Wear safety glasses with side shields (or goggles).

Hand protection

:

Chemical resistant gloves.

Other

:

Wear suitable protective clothing.

Respiratory protection

:

In case of inadequate ventilation use suitable respirator. Chemical respirator with organic vapor cartridge.

Hygiene measures

:

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Provide eyewash station and safety shower. Avoid contact with eyes, skin, and clothing.



MATERIAL SAFETY DATA SHEET

Version :02

PRODUCT NAME: iso-BUTANOL (iso-BUTYL ALCOHOL)

CAS Number: 78-83-1

9. PHYSICAL AND CHEMICAL PROPERTIES:

Appearance	: Clear colourless liquid.
Odor	: Alcohol-like
Solubility	: No data available.
Formula	: C ₄ H ₁₀ O
Molecular Weight	: 74.12 g/mol
Density	: 0.801 - 0.804 g at 20°C
pH	: No data available.
% Volatiles by volume @ 21C (70F)	: No data available.
Boiling Point	: 108°C
Melting Point	: -108°C
Flash Point	: 28 °C
Vapor Density (Air=1)	: 2.55
Vapor Pressure (mm Hg)	: 8 hPa at 20 °C
Evaporation Rate (BuAc=1)	: No data available.

10. STABILITY AND REACTIVITY:

Reactivity	: Vapor/air-mixtures are explosive at intense warming.
Chemical stability	: Material is stable under ambient conditions..
Possibility of hazardous reactions	Exothermic reaction with: Acid chlorides, strong reducing agents. Risk of ignition or formation of inflammable gases or vapours with: chromium(VI) oxide, Strong oxidizing agents, Aluminum. Violent reactions possible with: Alkali metals, Alkaline earth metals.
Conditions to avoid	: Heating.
Incompatible materials	: No data available.
Hazardous decomposition products	: In the event of fire: see section 5

11. TOXICOLOGICAL INFORMATION:

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral Product	: LD 50 Rat - female - 3.350 mg/kg
Dermal Product	: LD 50 Rabbit - female - 2.460 mg/kg
Inhalation Product	: LC 50 Rat - male and female - 6 h - > 18,18 mg/l - vapor



MATERIAL SAFETY DATA SHEET

Version :02

PRODUCT NAME: iso-BUTANOL (iso-BUTYL ALCOHOL)

CAS Number: 78-83-1

Repeated dose toxicity Product	: No data available.
Skin corrosion/irritation Product	: Causes skin irritation.
Serious eye damage/eye irritation Product	: Corrosive.
Respiratory or skin sensitization Product	: No data available.
Carcinogenicity Product	: This substance has no evidence of carcinogenic properties
IARC Monographs on the Evaluation of Carcinogenic Risks to Humans	: No carcinogenic components identified.
US. National Toxicology Program (NTP) Report on Carcinogens	: No carcinogenic components identified.
US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)	: No carcinogenic components identified.
Germ cell mutagenicity	: No data available.
Reproductive toxicity Product	: No components toxic to reproduction.
Specific target organ toxicity - single exposure Product	: May cause respiratory irritation. - Respiratory Tract. May cause drowsiness or dizziness. - Central nervous system.
Specific target organ toxicity - repeated exposure Product	: No data available.
Aspiration hazard Product	: No data available.
Other effects	: No data available.

12. ECOLOGICAL INFORMATION:**Ecotoxicity****Acute hazards to the aquatic environment**

Fish Product	: Flow-through test LC50 - Pimephales promelas (fathead minnow) - 1.430 mg/l - 96 h
Aquatic invertebrates Product	: Static test EC50 - Daphnia pulex (Water flea) - 1.100 mg/l - 48 h
Toxicity to algae	: Static test ErC50 - Pseudokirchneriella subcapitata - 1.799 mg/l - 72 h

Chronic hazards to the aquatic environment

Fish Product	: No data available.
Aquatic invertebrates Product	: NOEC - Daphnia magna (Water flea) - 20 mg/l - 21 d



MATERIAL SAFETY DATA SHEET

Version :02

PRODUCT NAME: iso-BUTANOL (iso-BUTYL ALCOHOL)

CAS Number: 78-83-1

Toxicity to Aquatic Plants	:	No data available.
Product:		
Persistence and degradability		
Biodegradation Product	:	Readily biodegradable.
BOD/COD ratio Product	:	No data available.
Bioaccumulative potential		
Bioconcentration factor (BCF) Product	:	No data available on bioaccumulation.
Partition coefficient n-octanol / water (log Kow) Product	:	No data available.
Mobility in soil	:	No data available.
Other adverse effects	:	No data available.

13. DISPOSAL CONSIDERATION:

Disposal instructions	:	Discharge, treatment, or disposal may be subject to national, state, or local laws. Disposal recommendations are based on uncontaminated material.
Contaminated packaging	:	Since emptied containers retain product residue, follow label warnings even after container is emptied.

14. TRANSPORT INFORMATION:

	UN No.	UN proper shipping name	Hazard Class(es)	Packaging group	Marine Pollutant
ADR/RID	UN 1212	Iso-Butanol (Iso-Butyl alcohol)	3	III	No
IMDG	UN 1212	Iso-Butanol (Iso-Butyl alcohol)	3	III	No
IATA	UN 1212	Iso-Butanol (Iso-Butyl alcohol)	3	III	No

15. REGULATORY INFORMATION:

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.
Safety, health and environmental regulations/legislation specific for the substance or mixture
No Data Available.

MATERIAL SAFETY DATA SHEET


Version :02

PRODUCT NAME: iso-BUTANOL (iso-BUTYL ALCOHOL)

CAS Number: 78-83-1

16. OTHER INFORMATION:

NFPA Hazard ID



Hazard rating: 0 - Minimal; 1 - Slight; 2 - Moderate; 3 - Serious; 4 - Severe

Issue Date : 21/09/2026

Version : 02

Disclaimer: This Material Safety Data Sheet (MSDS) is for guidance and is based upon information and tests believed to be reliable. ADVENT CHEMBIO PRIVATE LIMITED makes no guarantee of the accuracy or completeness of the data and shall not be liable for any damages relating thereto. The data is offered solely for your consideration, investigation, and verification. The data should not be confused with local, state, federal or insurance mandates, regulations, or requirements and CONSTITUTE NO WARRANTY. Any use of this data and information must be determined by the technical instructor in accordance with applicable local, state or federal laws and regulations. The conditions or methods of handling, storage, use and disposal of the product(s) described are beyond the control of ADVENT CHEMBIO PRIVATE LIMITED and may be beyond our knowledge. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH THE HANDLING, STORAGE, USE OR DISPOSAL OF THIS PRODUCT(S).