

Pg. 1 of 8

MATERIAL SAFETY DATA SHEET

Version:01

PRODUCT NAME: TOLUENE

1. IDENTIFICATION:

Product Code

90050, 90261, 90579, 90580, 90727, 90819, 91177, 91829, 93431, 94114, 94031, 94270,

CAS Number: 108-88-3

94152, 96077, 98101

Company Name : ADVENT CHEMBIO PRIVATE LIMITED

Address W-279, MIDC, TTC INDUSTRIAL AREA, THANE-BELAPUR ROAD, RABALE,

NAVI MUMBAI - 400 701.

E-mail : sales@adventchembio.com

WEBSITE : <u>www.adventchembio.com</u>

Company Phone Number : 022-27690837

2. HAZARDS IDENTIFICATION:

Hazard classification

Physical hazards

Flammable liquids : Category 2

Health hazards

Skin irritation : Category 2

Reproductive toxicity: Category 2

Specific target organ

toxicity - single exposure,

Oral

Specific target organ

tovicity repeated

toxicity - repeated

exposure, Oral

: Category 2

: Category 3

Aspiration hazard

Long-term (chronic) aquatic

hazard

: Category 1
: Category 3

Labels elements :

Hazard symbol :

Signal word : Danger

Hazard statement Highly flammable liquid and vapor.

May be fatal if swallowed and enters airways.

May cause drowsiness or dizziness.

Causes skin irritation.

Suspected of damaging the unborn child.

May cause damage to organs (Central nervous system) through prolonged or repeated

exposure.

Harmful to aquatic life with long lasting effects.



MATERIAL SAFETY DATA SHEET

CAS Number: 108-88-3

Version:01

Pg. 2 of 8

Precautionary statement

PRODUCT NAME: TOLUENE

Prevention Obtain special instructions before use.

Do not breathe dust/ fume/ gas/ mist/ vapors/ spray. Do not handle until all safety

precautions have been read and understood.

Wear protective gloves/ protective clothing/ eye protection/ face protection.

Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools. Take precautionary measures against static discharge.

IF exposed or concerned: Get medical advice/ attention. Response

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/

shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

Store in a dry & well-ventilated place. Keep container tightly closed. Containers which are Storage

opened must be carefully resealed and kept upright to prevent leakage.

Disposal Dispose of contents/container to an appropriate treatment and disposal facility in

accordance with applicable laws and regulations, and product characteristics at time of

disposal.

Other hazards which do not :

result in GHS classification

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at

levels of 0.1% or higher.

COMPOSITION/INFORMATION ON INGRADIENTS:

Ingredient	CAS Number	Percent	Hazardous
Toluene	108-88-3	NLT 99.0%	Yes

FIRST AID MEASURES:

General information : Get medical advice/attention if you feel unwell. Show this safety data sheet to the doctor in

attendance.

Call a physician or poison control center immediately. Rinse mouth. Do NOT induce Ingestion

vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the

Move to fresh air. Call a physician or poison control center immediately. If breathing stops,

Inhalation provide artificial respiration. If breathing is difficult, give oxygen.

Get medical attention if symptoms persist.

Skin contact Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact

lenses. Get medical attention.

Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact Eye contact

lenses. Get medical attention.

Most important symptoms/effects, acute

and delayed

The most important known symptoms and effects are described in the labelling (see section

2.)



MATERIAL SAFETY DATA SHEET

Pg. 3 of 8

Version:01

PRODUCT NAME: TOLUENE

Indication of immediate medical attention and special treatment needed

: No data available.

FIRE FIGHTING MEASURES:

General information : Flammable liquid and vapor.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media

Water spray, foam, dry powder or carbon dioxide.

Unsuitable extinguishing

media

Avoid water in straight hose stream; will scatter and spread fire.

Specific hazards arising from the chemical

Vapors may cause a flash fire or ignite explosively. Vapors may travel considerable distance

CAS Number: 108-88-3

to a source of ignition and flash back. Prevent buildup of vapors or gases to explosive concentrations. Vapor from the solvent may accumulate in container headspace resulting in

flammability hazard. Heat may cause the containers to explode.

Special protective equipment and precautions for firefighters

Special firefighting

procedures

Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting

the fire. Fight fire from a protected location. Move containers from fire area if you can do so

without risk.

Special protective

equipment for fire-fighters

Firefighters must use standard protective equipment including flame retardant coat, helmet

with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

ACCIDENTAL RELEASE MEASURES:

Personal precautions, protective equipment and emergency procedures

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Avoid breathing mists or vapors. Keep upwind. Ventilate closed spaces before entering them. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

Methods and material for containment and cleaning up

Eliminate all ignition sources if safe to do so. Use only non-sparking tools. Take precautionary measures against static discharges. Stop leak if possible without any risk.

Absorb spill with vermiculite or other inert material, then place in a container for chemical waste. Clean surface thoroughly to remove residual contamination. Dike far ahead of larger spill for later recovery and disposal.

Notification Procedures

Prevent entry into waterways, sewer, basements or confined areas. Inform authorities if large amounts are involved.

Environmental precautions

Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

HANDLING AND STORAGE:

Precautions for safe handling

Do not handle until all safety precautions have been read and understood. DO NOT handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Take precautionary measures against static discharges. Ground/bond receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Wear protective



Pg. 4 of 8

MATERIAL SAFETY DATA SHEET

Version:01

PRODUCT NAME: TOLUENE

gloves/protective clothing/eye

Protection / face protection. Avoid contact with eyes, skin, and clothing. Do not breathe mist or vapor. Use only with adequate ventilation. Wash hands thoroughly after handling. Keep away from food, drink and animal feeding stuffs. Keep container tightly closed in a dry, well-ventilated place. Ground container and transfer equipment to eliminate static electric sparks. Comply with all national, state, and local codes pertaining to the storage, handling, dispensing, and disposal of flammable liquids.

CAS Number: 108-88-3

Conditions for safe storage, including any incompatibilities

8. EXPOSURE CONTROLS PERSONAL PROTECTION:

Control parameters

Ingredients with workplace control parameters :-

Application Area	Routes of exposure	Health effect	Value	
Workers	Inhalation	Acute systemic effects	384 mg/m3	
Workers	Inhalation	Acute local effects	384 mg/m3	
Workers	Skin contact	Long-term systemic effects	384mg/kg BW/d	
Workers	Inhalation	Long-term systemic effects	192 mg/m3	
Workers	Inhalation	Long-term local effects	192 mg/m3	
Consumers	Inhalation	Acute systemic effects	226 mg/m3	
Consumers	Inhalation	Acute local effects	226 mg/m3	
Consumers	Skin contact	Long-term systemic effects	226mg/kg BW/d	
Consumers	Inhalation	Long-term systemic effects	56,5 mg/m3	
Consumers	Inhalation	Long-term systemic effects	8,13mg/kg BW/d	
Compartment	npartment Value			
Soil		2,89 mg/kg		
Sea water		0,68 mg/l		
Fresh water		0,68 mg/l		
Sea sediment		16,39 mg/kg		
Fresh water sediment		16,39 mg/kg		
Sewage treatment plant		13,61 mg/l		
Aquatic intermittent release		0,68 mg/l		

Derived No Effect Level (DNEL)

Predicted No Effect
Concentration (PNEC)

Appropriate engineering

controls : No data available

Individual protection measures, such as personal protective equipment

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. An eye wash and safety shower must be available in the immediate work

General information



MATERIAL SAFETY DATA SHEET

Pg. 5 of 8 Version :01

CAS Number: 108-88-3

PRODUCT NAME: TOLUENE

area. Use explosion-proof ventilation equipment.

Eye/face protection . Wear safety glasses with side shields (or goggles).

Hand protection . Chemical resistant gloves.

Other . Wear suitable protective clothing.

Respiratory protection In case of inadequate ventilation use suitable respirator. Chemical

respirator with organic vapor cartridge.

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and

protective equipment to remove contaminants. Provide eyewash station and safety shower.

Avoid contact with eyes, skin, and clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES:

Appearance : Clear, colourless, refracting liquid.

Odor : Benzene-like

Solubility : 0,58 g/l at 25 °C - partly soluble in water

Molecular Weight : 92.14 g/mol

Specific Gravity : 0.864 - 0.867 g/cm3 at 20°C

pH : Not applicable.

% Volatiles by volume @

Hygiene measures

21C (70F)

No data available.

Boiling Point : 110 - 111°C

 Melting Point
 : -93°C

 Flash Point
 : 4,4 °C

 Vapor Density (Air=1)
 : 3.18

Vapor Pressure (mm Hg) : 30,88 hPa at 21,1 °C Evaporation Rate (BuAc=1) : No data available.

10. STABILITY AND REACTIVITY:

Reactivity : Vapors may form explosive mixture with air.

Chemical stability : Material is stable under ambient conditions..

Risk of explosion with: fuming sulfuric acid Nitric acid silver perchlorates nitrogen dioxide

Possibility of hazardous

reactions

nonmetallic halides halogen-halogen compounds uranium hexafluoride organic nitro compounds Violent reactions possible with: Strong acids Strong oxidizing agents sulfur with

Heat.



MATERIAL SAFETY DATA SHEET

Pg. 6 of 8 Version:01

CAS Number: 108-88-3 **PRODUCT NAME: TOLUENE**

Conditions to avoid : Heat, sparks, flames. Sunlight.

Incompatible materials : Rubber, various plastics

Hazardous decomposition

In the event of fire: see section 5 products

11. TOXICOLOGICAL INFORMATION:

Information on likely routes of exposure

Ingestion : Irritating. May cause nausea, stomach pain and vomiting.

Inhalation May cause irritation to the mucous membranes and upper respiratory tract. May cause

central nervous system effects

Skin contact Causes mild skin irritation

Eye contact Causes serious eye irritation.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral Product : LD 50 Rat - male - 5.580 mg/kg

Dermal Product LD 50 Rabbit - > 5.000 mg/kg

Inhalation Product LC 50 Rat - male and female - 4 h - 25,7 mg/l - vapor

Repeated dose toxicity

Product

No data available.

Skin corrosion/irritation

Product

Prolonged or repeated skin contact may cause drying, cracking, or irritation

Serious eye damage/eye

irritation Product

Irritating to eyes.

Respiratory or skin

sensitization Product

: Not a skin sensitizer.

Carcinogenicity Product

This substance has no evidence of carcinogenic properties

IARC Monographs on the

Evaluation of Carcinogenic

: No carcinogenic components identified.

Risks to Humans

US. National Toxicology

Program (NTP) Report on

: No carcinogenic components identified.

Carcinogens

US. OSHA Specifically

Regulated Substances (29 CFR 1910.1001-1050

Germ cell mutagenicity

: No carcinogenic components identified.

In vitro Product

: No data available.



Pg. 7 of 8

Version:01

MATERIAL SAFETY DATA SHEET

CAS Number: 108-88-3 **PRODUCT NAME: TOLUENE**

Reproductive toxicity

Product

: Suspected of damaging the unborn child.

Specific target organ

toxicity - single exposure

Aspiration hazard Product

Product

: May cause drowsiness or dizziness. - Central nervous system

Specific target organ

toxicity - repeated

May cause damage to organs through prolonged or repeated exposure. - Central nervous system

exposure Product

Aspiration may cause pulmonary edema and pneumonitis.

Other effects No data available.

12. ECOLOGICAL INFORMATION:

Ecotoxicity

Acute hazards to the aquatic environment

Fish Product

: LC50 - Oncorhynchus kisutch (coho salmon) - 5,5 mg/l.

Aquatic invertebrates

EC50 - Ceriodaphnia dubia (water flea) - 3,78 mg/l - 48 h. **Product**

Chronic hazards to the aquatic environment

Fish Product

: No data available.

Aquatic invertebrates

Product

No data available.

Toxicity to Aquatic Plants

No data available.

Product:

Persistence and degradability

Biodegradation Product

: 86 % - Readily biodegradable.

BOD/COD ratio Product

No data available.

Bioaccumulative potential

Bioconcentration factor

(BCF) Product

No data available on bioaccumulation.

Partition coefficient n-

: No data available.

octanol / water (log Kow)

Product Mobility in soil

No data available.

Other adverse effects

No data available.

13. DISPOSAL CONSIDERATION:

Disposal instructions

: Discharge, treatment, or disposal may be subject to national, state, or local laws. Disposal

recommendations are based on uncontaminated material.



Pg. 8 of 8

MATERIAL SAFETY DATA SHEET

Version:01

PRODUCT NAME: TOLUENE

CAS Number: 108-88-3

Contaminated packaging

Since emptied containers retain product residue, follow label warnings even after container is emptied.


14. TRANSPORT INFORMATION:

DOT	UN No. UN 1294	UN proper shipping name Toluene	Hazard Class(es) 3	Packaging group II	Marine Pollutant No
IMDG	UN 1294	Toluene	3	II	No
IATA	UN 1294	Toluene	3	II	No

15. REGULATORY INFORMATION:

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006. Safety, health and environmental regulations/legislation specific for the substance or mixture No Data Available.

16. OTHER INFORMATION:



Hazard rating: 0 - Minimal; 1 - Slight; 2 - Moderate; 3 - Serious; 4 - Severe

Issue Date : 13/06/2023

Version : 01

Disclaimer: This Material Safety Data Sheet (MSDS) is for guidance and is based upon information and tests believed to be reliable. ADVENT CHEMBIO PRIVATE LIMITED makes no guarantee of the accuracy or completeness of the data and shall not be liable for any damages relating thereto. The data is offered solely for your consideration, investigation, and verification. The data should not be confused with local, state, federal or insurance mandates, regulations, or requirements and CONSTITUTE NO WARRANTY. Any use of this data and information must be determined by the technical instructor in accordance with applicable local, state or federal laws and regulations. The conditions or methods of handling, storage, use and disposal of the product(s) described are beyond the control of ADVENT CHEMBIO PRIVATE LIMITED and may be beyond our knowledge. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH THE HANDLING, STORAGE, USE OR DISPOSAL OF THIS PRODUCT(S).