

Pg. 1 of 8

MATERIAL SAFETY DATA SHEET

CAS Number: 141-78-6

Version:01

PRODUCT NAME: ETHYL ACETATE

1. IDENTIFICATION:

Product Code : 90021, 90785, 90162, 90406, 90891, 91632, 94029, 94262, 95202, 98709, 98111

Company Name : ADVENT CHEMBIO PRIVATE LIMITED

Address W-279, MIDC, TTC INDUSTRIAL AREA, THANE-BELAPUR ROAD, RABALE,

NAVI MUMBAI - 400 701.

E-mail : sales@adventchembio.com

WEBSITE : www.adventchembio.com

Company Phone Number : 022-27690837

2. HAZARDS IDENTIFICATION:

Hazard classification

Physical hazards

Flammable liquids : Category 2

Health hazards

Skin corrosion/irritation : Category 3

Serious eye damage /Eye irritation : Category 2

Specific target organ toxicity - single

exposure

Hazard symbol

Signal word

: Category 3

Danger

Labels elements :

Hazard statement Highly flammable liquid and vapor.

Causes serious eye irritation.

May cause respiratory irritation.
May cause drowsiness or dizziness.

Precautionary statement

Prevention : Obtain special instructions before use.

Do not breathe dust/ fume/ gas/ mist/ vapors/ spray. Do not handle

until all safety precautions have been read and understood.

Wear protective gloves/ protective clothing/ eye protection/ face

protection.

Keep away from heat/ sparks/ open flames/ hot surfaces. No

smoking.

Keep container tightly closed. Ground/ bond container and receiving

equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.



Pg. 2 of 8

MATERIAL SAFETY DATA SHEET

Version:01

PRODUCT NAME: ETHYL ACETATE

Use only non-sparking tools. Take precautionary measures against static discharge.

CAS Number: 141-78-6

Response : IF exposed or concerned: Get medical advice/ attention. In case of

fire: Use water spray, foam, dry powder or carbon dioxide for

extinction.

IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/ shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

IF INHALED: Remove person to fresh air and keep comfortable for

breathing.

IF SWALLOWED: Immediately call a POISON CENTER or

doctor/physician.

Storage : Store at ambient temperature in a dry and well ventilated place.

Keep container tightly closed. Containers which are opened must be

carefully resealed and kept upright to prevent leakage.

Disposal : Dispose of contents/container to an appropriate treatment and

disposal facility in accordance with applicable laws and regulations,

and product characteristics at time of disposal.

Other hazards which do not result in GHS

classification

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite

liquid and vapor. May cause flash fire or explosion.

2. COMPOSITION/INFORMATION ON INGRADIENTS:

Ingredient	CAS Number	Percent	Hazardous
Ethyl Acetate	141-78-6	99 - 100%	Yes

3. FIRST AID MEASURES:

General information : Get medical advice/attention if you feel unwell. Show this safety data sheet to the doctor in

attendance.

Ingestion Call a physician or poison control center immediately. Rinse mouth. Do NOT induce

: vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the

lungs.

Move to fresh air. Call a physician or poison control center immediately. If breathing stops,

Inhalation : provide artificial respiration. If breathing is difficult, give oxygen.

Get medical attention if symptoms persist.

Skin contact . Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact

lenses. Get medical attention.

Eye contact Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact

lenses. Get medical attention.

Most important

symptoms/effects, acute

and delayed

Indication of immediate medical attention and

special treatment needed

: Irritating to eyes, respiratory system and skin.

: Symptoms may be delayed. Treat symptomatically.



MATERIAL SAFETY DATA SHEET

Pg. 3 of 8 Version:01

PRODUCT NAME: ETHYL ACETATE CAS Number: 141-78-6

FIRE FIGHTING MEASURES:

Flammable liquid and vapor. General information

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media

Water spray, foam, dry powder or carbon dioxide.

Unsuitable extinguishing

media

Avoid water in straight hose stream; will scatter and spread fire.

Specific hazards arising

from the chemical

Vapors may cause a flash fire or ignite explosively. Vapors may travel considerable distance to a source of ignition and flash back. Prevent buildup of vapors or gases to explosive

concentrations. Vapor from the solvent may accumulate in container headspace resulting in

flammability hazard. Heat may cause the containers to explode.

Special protective equipment and precautions for firefighters

Special firefighting

procedures

Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a protected location. Move containers from fire area if you can do so

without risk.

Special protective

equipment for fire-fighters

Firefighters must use standard protective equipment including flame retardant coat, helmet

with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

ACCIDENTAL RELEASE MEASURES:

Personal precautions, protective equipment and emergency procedures

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Avoid breathing mists or vapors. Keep upwind. Ventilate closed spaces before entering them. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

Methods and material for containment and cleaning

up

Eliminate all ignition sources if safe to do so. Use only non-sparking tools. Take precautionary measures against static discharges. Stop leak if possible without any risk.

Absorb spill with vermiculite or other inert material, then place in a container for chemical waste. Clean surface thoroughly to remove residual contamination. Dike far ahead of larger

spill for later recovery and disposal.

Notification Procedures

Prevent entry into waterways, sewer, basements or confined areas. Inform authorities if large amounts are involved.

Environmental precautions

Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

HANDLING AND STORAGE:

Precautions for safe handling

Do not handle until all safety precautions have been read and understood. DO NOT handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Take precautionary measures against static discharges. Ground/bond

container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting/equipment. Use only non-sparking tools. Wear protective

gloves/protective clothing/eye

protection/ face protection. Avoid contact with eyes, skin, and clothing. Do not breathe mist or vapor. Use only with adequate ventilation. Wash hands thoroughly after handling.

Conditions for safe storage,

including any

Keep away from food, drink and animal feeding stuffs.

Store at ambient temperature in a dry and well ventilated place.



Pg. 4 of 8

MATERIAL SAFETY DATA SHEET

Version:01

PRODUCT NAME: ETHYL ACETATE

CAS Number: 141-78-6

incompatibilities

Keep the container tightly closed, away from heat. Containers which are opened must be

carefully resealed and kept upright to prevent leakage.

Ground container and transfer equipment to eliminate static electric sparks. Comply with all national, state, and local codes pertaining to the storage, handling, dispensing, and disposal

of flammable liquids.

7. EXPOSURE CONTROLS PERSONAL PROTECTION:

Control parameters

Occupational exposure

limits

Chemical identity Type Exposure Limit values Source

Ethyl Acetate TWA 400 ppm US. ACGIH Threshold Limit Values

(2011)

REL 400 ppm 1400 mg/m³ US. NIOSH: Pocket Guide to Chemical

Hazards (2010)

PEL 400 ppm 1400 mg/m³ US. OSHA Table Z-1 Limits for Air

Contaminants (29 CFR 1910.1000) (02

2006

TWA 400 ppm 1400 mg/m³ US. OSHA Table Z-1-A (29 CFR

1910.1000)(1989)

Appropriate engineering

General information

controls : No data available

Individual protection measures, such as personal protective equipment

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust

ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an

acceptable level. An eye wash and safety shower must be available in the immediate work

 $area. \ Use \ explosion-proof \ ventilation \ equipment.$

Eye/face protection. Wear safety glasses with side shields (or goggles).

Hand protection . Chemical resistant gloves.

Other : Wear suitable protective clothing.

Respiratory protection In case of inadequate ventilation use suitable respirator. Chemical

respirator with organic vapor cartridge.

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and

Hygiene measures protective equipment to remove contaminants. Provide eyewash station and safety shower.

Avoid contact with eyes, skin, and clothing.



MATERIAL SAFETY DATA SHEET

Pg. 5 of 8 Version:01

CAS Number: 141-78-6 PRODUCT NAME: ETHYL ACETATE

8. PHYSICAL AND CHEMICAL PROPERTIES:

Appearance : Clear, colorless liquid

Odor Characteristics

Solubility No data available

: CH₃COOC₂H₅ **Formula**

Molecular Weight : 88.11 g/mol

: 0.899 - 0.901 g/cm3 at 20°C **Specific Gravity**

No data available рΗ

% Volatiles by volume @

21C (70F)

No data available

Boiling Point 77°C **Melting Point** -83°C **Flash Point** -4°C

Vapor Density (Air=1) 3.04

Vapor Pressure (mm Hg) 12.4 kPa @ 25°C Evaporation Rate (BuAc=1)

No data available

9. STABILITY AND REACTIVITY:

Reactivity No dangerous reaction known under conditions of normal use.

Chemical stability Material is stable under ambient conditions..

Possibility of hazardous

reactions

Hazardous polymerization does not occur.

Conditions to avoid Heat, sparks, flames. Sunlight.

Strong oxidizing agents. Strong alkalis. Strong acids. Nitrates. May attack some plastics, Incompatible materials

rubber and coatings.

Hazardous decomposition

products

Thermal decomposition may release oxides of carbon.

10. TOXICOLOGICAL INFORMATION:

Information on likely routes of exposure

Ingestion : Irritating. May cause nausea, stomach pain and vomiting.

Inhalation : May cause irritation to the respiratory system. May cause drowsiness or dizziness.

Skin contact Causes mild skin irritation

Eye contact : Causes serious eye irritation.



Pg. 6 of 8

MATERIAL SAFETY DATA SHEET

CAS Number: 141-78-6

Version:01

PRODUCT NAME: ETHYL ACETATE

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral Product : LD 50 (Rat): 5.6 g/kg

Dermal Product : LD 50 (Rabbit): > 18,000 mg/kg.

Inhalation Product LD 50 (Mouse, 4 h): 1,500 mg/l

Repeated dose toxicity

Product

No data available.

Skin corrosion/irritation

Product

Causes mild skin irritation.

Serious eye damage/eye

irritation Product

: Causes serious eye irritation.

Respiratory or skin

sensitization Product

: Not a skin sensitizer.

No data available.

Carcinogenicity Product

: This substance has no evidence of carcinogenic properties

IARC Monographs on the

Evaluation of Carcinogenic

Risks to Humans

US. National Toxicology

Program (NTP) Report on

Carcinogens

US. OSHA Specifically

Regulated Substances (29

CFR 1910.1001-1050 Germ cell mutagenicity : No carcinogenic components identified.

: No carcinogenic components identified.

No carcinogenic components identified.

In vitro Product

Reproductive toxicity

Product

No components toxic to reproduction.

Narcotic effect. Respiratory tract irritation.

Specific target organ

toxicity - single exposure

Product

Specific target organ

toxicity - repeated

None known.

exposure Product

Aspiration hazard Product

: May be harmful if swallowed and enters airways .

Other effects

None known.



MATERIAL SAFETY DATA SHEET

Pg. 7 of 8 Version :01

PRODUCT NAME: ETHYL ACETATE CAS Number: 141-78-6

11. ECOLOGICAL INFORMATION:

Ecotoxicity

Acute hazards to the aquatic environment

Fish Product

ETHYL ACETATE

: No data available.

Specified substance(s):

LC 50 (Fathead minnow (Pimephales promelas), 96 h): 220 - 250 mg/l Mortality LC 50 (Rainbow trout, donaldson trout (Oncorhynchus mykiss), 96 h): 352 - 500 mg/l

· Mortality

LC 50 (Carp (Leuciscus idus melanotus), 48 h): 270 mg/l Mortality

Aquatic invertebrates

Product

: No data available.

Specified substance(s):

: EC 50 (Brine shrimp (Artemia salina), 24 h): 306.9 - 389.9 mg/l Intoxication

ETHYL ACETATE

LC 50 (Hydra (Hydra oligactis), 48 h): 1,350 mg/l Mortality LC 50 (Water flea (Daphnia cucullata), 48 h): 154 mg/l Mortality

Chronic hazards to the aquatic environment

Fish Product

: No data available.

Aquatic invertebrates

Product

No data available.

Toxicity to Aquatic Plants

Product:

: No data available.

Persistence and degradability

Biodegradation Product

Expected to be readily biodegradable.

BOD/COD ratio Product

No data available.

Bioaccumulative potential

Bioconcentration factor

(BCF) Product

No data available on bioaccumulation.

Partition coefficient n-

octanol / water (log Kow)

Product

: Log Kow: 0.73

Mobility in soil

: The product is partly soluble in water. May spread in the aquatic environment.

Other adverse effects

The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging

effect on the environment.

12. DISPOSAL CONSIDERATION:

Disposal instructions

: Discharge, treatment, or disposal may be subject to national, state, or local laws. Disposal recommendations are based on uncontaminated material.

Contaminated packaging

Since emptied containers retain product residue, follow label warnings even after container

is emptied.



MATERIAL SAFETY DATA SHEET

CAS Number: 141-78-6

Pg. 8 of 8

Version:01

PRODUCT NAME: ETHYL ACETATE


13.	TRAN	SPORT	INFORM	ATION:

DOT	UN No. UN 1173	UN proper shipping name Ethyl Acetate	Hazard Class(es) 3	Packaging group II	Marine Pollutant No
IMDG	UN 1173	Ethyl Acetate	3	II	No
IATA	UN 1173	Ethyl Acetate	3	II	No

14. REGULATORY INFORMATION:

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006. Safety, health and environmental regulations/legislation specific for the substance or mixture No Data Available.

15. OTHER INFORMATION:



Hazard rating: 0 - Minimal; 1 - Slight; 2 - Moderate; 3 - Serious; 4 - Severe

Issue Date : 29/06/2023

Version : 01

Disclaimer: This Material Safety Data Sheet (MSDS) is for guidance and is based upon information and tests believed to be reliable. ADVENT CHEMBIO PRIVATE LIMITED makes no guarantee of the accuracy or completeness of the data and shall not be liable for any damages relating thereto. The data is offered solely for your consideration, investigation, and verification. The data should not be confused with local, state, federal or insurance mandates, regulations, or requirements and CONSTITUTE NO WARRANTY. Any use of this data and information must be determined by the technical instructor in accordance with applicable local, state or federal laws and regulations. The conditions or methods of handling, storage, use and disposal of the product(s) described are beyond the control of ADVENT CHEMBIO PRIVATE LIMITED and may be beyond our knowledge. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH THE HANDLING, STORAGE, USE OR DISPOSAL OF THIS PRODUCT(S).